

HYDRAULIC OT TABLE



Hydraulic OT Table (ME-500H)

Features

- Hydraulic and Mechanical Operated.
- Rust proof / SS 304
- Concealed pump.
- Centric base made from high quality stainless steel.
- Leg & Head section are interchangeable.
- Centric pillars, Stainless fitting.
- Detachable head, leg and pelvic section.
- inbuilt kidney bridge.
- Base and cover made of attractive, easy to clean stainless steel.
- Sophisticated mechanics provide smooth, stepless articulation of the table top for precise patient positioning.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 520mm (W)
- **Height Adjustment** : 762mm - 1000 mm
- **Trendelenbrug / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 150 mm
- **Back Rest (up / down)** : 80° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Patient Weight Capacity** : 150 Kgs



Hydraulic OT Table (ME-600H)

Features

- Table top is made with stainless steel grade 304 to avoid rust with canceled pump.
- The five section Stainless Steel table top is equipped with removable, antistatic mattresses.
- All the positions are realized by a mechanical driver.
- The table is furnished with hard, robust stainless steel shell which provides the sense of dirt free & sanitized operations.
- Precision made hydraulic system with a single lever action hydraulic life controlled by a foot pedal.
- Five section stainless steel top gives anatomic adaptation to the patient body.
- Inbuilt Kidney Bridge and large perinea cut out for drainage.
- Manual floor locking system.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 520mm (W)
- **Height Adjustment** : 762mm - 1000 mm
- **Trendelenbrug / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 150 mm
- **Back Rest (up / down)** : 80° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Patient Weight Capacity** : 200 Kgs

NOTE : DUE TO OUR CONTINUOUS R & D PROGRAM SPECIFICATIONS AND DESIGN MAY CHANGE WITHOUT PRIOR NOTICE.



HYDRAULIC OT TABLE



Hydraulic OT Table (ME-800H) C Arm compatible

Features

- Hydraulic and Mechanical Operated.
- Rust proof/ SS 304
- Concealed pump.
- The base is eccentric for trouble-free C-ARM movements.
- Leg & Head section are interchangeable.
- Eccentric pillars, Stainless fitting.
- Detachable head, leg and pelvic section.
- inbuilt kidney bridge.
- Five sectional radio-translucent.
- Base and cover made of attractive, easy to clean stainless steel.
- Sophisticated mechanics provide smooth, stepless articulation of the table top for precise patient positioning.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 520mm (W)
- **Height Adjustment** : 762mm - 1000 mm
- **Trendelenbrug / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 150 mm
- **Back Rest (up / down)** : 80° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Patient Weight Capacity** : 200 Kgs

NOTE : DUE TO OUR CONTINUOUS R & D PROGRAM SPECIFICATIONS AND DESIGN MAY CHANGE WITHOUT PRIOR NOTICE.

ELECTRIC OT TABLE



OBSTETRIC GYNEC TABLE (C-1790G)

In terms of quality, reliability and functionality Operating Table is being acknowledged as the ideal solution for Gynecology and Obstetrics. Due to its modular design, can be flexibly adapted to your needs and configured to suit your exact surgical requirements. C Cube Hydraulic operation table for gynecology and obstetrics. With full affinity profile. Pink color is available for the mattress. It overcomes the slow speed of similar products.

Advantages

- SS-304
- Surgeons Panel
- Floor Locking
- Zero Positioning

Technical Specifications

- **Top Dimension** : 1630mm (L) x 550mm (W)
- **Height Adjustment** : 680mm - 1090 mm
- **Seat Plate (down / up)** : 8° / 15°
- **Back Plate (down / up)** : 70° / 10°
- **Battery Backup** : 2 – 3 Hours **(Optional)**
- **Mains Voltage** : AC 220V+10% 50Hz
- **Patient Weight Capacity** : 200 Kgs.



ELECTRIC OT TABLE



Electrical OT Table (ME-1000E)

Features

- Fully electrically operated table, five sections, radio-translucent table top with eccentric pillars and Die Compressed base.
- Rust proof/ SS 304.
- Interchangeable head and leg sections (manually).
- All positions operated through cable remote.
- Inbuilt kidney bridge.
- Auto leveling (zero function).
- Indication of Battery Back provided in the hand set.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 520mm (W)
- **Height Adjustment** : 762mm - 1050 mm
- **Trendelenbrug / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 130 mm
- **Back Rest (up / down)** : 80° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Power Supply** : 24V DC
- **Battery Backup** : 2-3 Hours (optional)
- **Mains Voltage Capacity** : AC 220V+10%50Hz
- **Patient Weight Capacity** : 200 Kgs.



Advanced Electrical OT Table (ME-1500E)

- SS-304
- Surgeons Panel
- Electric (Remote Operated)
- C-Arm Compatible
- Floor Locking
- Zero Positioning

Features

- Fully electrically operated table, five sections, radio-translucent table top with eccentric pillars and Die Compressed base.
- Interchangeable head and leg sections (manually).
- All positions operated through cable remote.
- Electric floor locking. (Optional)
- Inbuilt kidney bridge.
- Auto leveling (zero function).
- We are providing two Handsets. Additional fixed control panel provided on the table top, which can be used in case of failure of main hand set.
- Indication of Battery Back provided in the hand set.
- Handset is providing Dual Memory Function which can be set and reset.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 522mm (W)
- **Height Adjustment** : 750mm - 1000 mm
- **Trendelenbrug / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 130 mm
- **Back Rest (up / down)** : 60° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Power Supply** : 24V DC
- **Battery Backup** : 2-3 Hours (optional)
- **Mains Voltage Capacity** : AC 220V+10%50Hz
- **Patient Weight Capacity** : 200 Kgs.

NOTE : DUE TO OUR CONTINUOUS R & D PROGRAM SPECIFICATIONS AND DESIGN MAY CHANGE WITHOUT PRIOR NOTICE.



ELECTRIC OT TABLE



Ophthalmic OT Table (ME-1800E)

Features

- Ophthalmic OT Table has a maximum height of 920 mm and minimum height of 690 mm.
- Ideal for standing table or sitting working position.
- It is an ideal operating table with the advantages of strong applicability, easy to operate.
- Adjusts conveniently and steady performance.
- Its ergonomic design ensures both surgeon and patient comfort.
- Patient comfort is assured with deep antiseptic cushions which are easy to clean.
- The adjustable cushioned head-rest ensures doctor comfort and resistant during operations.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 600mm(W)
- **Net Weight** : 120 Kgs
- **Minimum Height** : 690 mm
- **Maximum Height** : 920 mm
- **Stroke Length** : 230 mm
- **Patient Weight Capacity** : 150 Kg
- **Back Rest Section** : 20" (Head Side)
- **Leg Section** : 30"
- **Power Supply** : 24V DC
- **Battery Backup** : 2-3 Hours (optional)
- **Mains Voltage Capacity** : AC 220V+10%50Hz



Electro – Hydraulic OT Table (ME-2100HE)

Features

- Five section table top with divided foot section.
- Table top is constructed from a high-pressure laminate to permit x-ray penetration and fluoroscopy.
- All table positioning i.e. height, back section, lateral tilt, trendelenburg and anti-trendelenburg, operated by remote.
- The casings on the frame and centre supporting column should be made of hygienic stainless steel and should have built in elevator for kidney and chest bridge.
- Table Top is made from radiolucent material.

Technical Specifications

- **Top Dimension** : 1900mm(L) x 522mm (W)
- **Height Adjustment** : 750mm - 1050 mm
- **Trendelenburg / Reverse** : 30° / 25°
- **Lateral Tilt** : 20° / 20°
- **Kidney Elevator** : 130 mm
- **Back Rest (up / down)** : 60° / 25°
- **Leg Rest (up / down)** : 15° / 90°
- **Head Rest (up / down)** : 20° / 60°
- **Power Supply** : 24V DC
- **Battery Backup** : 2-3 Hours (optional)
- **Mains Voltage Capacity** : AC 220V+10%50Hz
- **Patient Weight Capacity** : 200 Kgs.

NOTE : DUE TO OUR CONTINUOUS R & D PROGRAM SPECIFICATIONS AND DESIGN MAY CHANGE WITHOUT PRIOR NOTICE.

